

## Basic features

Application	Ethernet
Approval/Conformity	CE WEEE cULus

## Electrical connection

Bending radius min., flexible cable	10 x D
Cable	TPE teal, 2 m, drag chain compatible
Cable diameter D	5.50 mm ±0.13 mm
Cable, bending cycles min.	1 mil.
Cable, note	Ethernet
Conductor cross-section	24 AWG
Connection 1	M12x1-Male, straight, 4-pin, D-coded
Connection 2	RJ45-Male, straight, 4-pin
Number of conductors	4
System	Molded/Molded

## Electrical data

Cable rated voltage AC max.	300 V
Cable rated voltage DC max.	300 V
Conductor construction	2x2 twisted-pair
Conductor resistance	≤ 26.0 Ohm/1000 ft
Coupling resistance max.	100 Ohm ±15 Ohm
Operating capacitance	13.5 pF/ft
Operating voltage Ub	42 VDC / 30 VAC
Rated current (40 °C)	1.0 A
Transfer rate	10/100 Mbit/s

## Environmental conditions

Cable temperature, flexible routing	-40...105 °C
IP rating	IP67, IP68, IP69K/IP20

## Material

Cable jacket, material	TPE
Cable shield	unshielded
Material contact carrier	PUR/PA
Material contacts	Brass, gold plated/Brass, gold plated
Material cover nut	Brass nickel-plated
Material grip	PUR/PVC


## Mechanical data

Cable jacket, color	teal
Cable length L	2.00 m
Cable properties	drag chain compatible
Tightening torque pigtail	0.6 Nm/-


Remarks

Cable construction per UL CMX Outdoor  
 Enclosure rating per IEC 60529 or ISO 20653, only in screwed state with the associated mating piece.

**Connector Drawings**



II  
 PIN 1: white/orange  
 PIN 2: orange  
 PIN 3: white/green  
 PIN 4: not used  
 PIN 5: not used  
 PIN 6: green  
 PIN 7: not used  
 PIN 8: not used



I  
 PIN 1: white/orange  
 PIN 2: white/green  
 PIN 3: orange  
 PIN 4: green

**Wiring Diagrams (Schematic)**

